



# MATERIAL SAFETY DATA SHEET

MSDS: CHAMPION® MSDS 200 SERIES LUBRICANTS

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### CHAMPION® MSDS 200 SERIES LUBRICANTS

**Synonyms:**

4025 CHAMPION® 2 CYCLE ENGINE OIL	4343 CHAMPION® BIA TC-W3
4090 CHAMPION® WP2 2 CYCLE RACE OIL	4425 INLINE - CHAMPION® 2 CYCLE OIL
4115 CHAMPION® 2 CYCLE POWER EQUIPMENT	4443 INLINE - CHAMPION® TC-W3

**Company Identification**

Champion Brands, L.L.C., 1001 Golden Drive, Clinton, MO 64735  
 PHONE: 800-821-5693 WEBSITE: [www.championbrands.com](http://www.championbrands.com)

<b>CAS Registry Number</b>	Not Applicable
<b>Synonyms</b>	None
<b>Generic/Chemical Name</b>	Mixture
<b>Product Type</b>	Petroleum Based Lubricating Oil
<b>Preparation Date</b>	March 2, 2004

**Transportation Emergency Response**

CHEMTREC: (800) 424-9300

**Product Information**

Product Information and MSDS Requests: (800) 821-5693 and [www.championbrands.com](http://www.championbrands.com)

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	AMOUNT
Highly refined BASE OIL (C15 - C50)	Mixture	45.0 – 90.0 %weight
Aliphatic Hydrocarbons	8052-41-3	0 - 25.00 %weight
ADDITIVES	Mixture	10.00 – 30.00 %weight

The BASE OIL may be a mixture of any of the following: CAS 64741884, CAS 64741895, CAS 64741964, CAS 64741975, CAS 64742014, CAS 64742525, CAS 64742536, CAS 64742547, CAS 64742558, CAS 64742570, CAS 64742627  
 The ADDITIVES are a mixture of confidential ingredients permitted by 29 CFR 1910.1200 and various State Right to Know Laws. In the event of medical emergency, specific chemical information will be disclosed to a treating physician or nurse.

## 3. HAZARD IDENTIFICATION

**IMMEDIATE HEALTH EFFECTS**

**Eye:** Not expected to cause prolonged or significant eye irritation.

**Skin:** Contact with the skin is not expected to cause prolonged or significant irritation. Not expected to be harmful to internal organs if absorbed through the skin.

**Ingestion:** Not expected to be harmful if swallowed.

**Inhalation:** Not expected to be harmful if inhaled. Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

## 4. FIRST AID MEASURES

**Eye:** No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

**Skin:** No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To

remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

**Ingestion:** No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

**Inhalation:** No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

## 5. FIRE FIGHTING MEASURES

### FIRE CLASSIFICATION:

OSHA Classification (29 CFR 1910.1200): Not classified by OSHA as flammable or combustible.

**NFPA RATINGS:** Health: 1 Flammability: 2 Reactivity: 0

### FLAMMABLE PROPERTIES:

**Flashpoint:** 72°C (162°F) (Min) ASTM D93 PMCC

**Autoignition:** NDA

**Flammability (Explosive) Limits (% by volume in air):** Lower: NA Upper: NA

**EXTINGUISHING MEDIA:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

### PROTECTION OF FIRE FIGHTERS:

**Fire Fighting Instructions:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames. This material will burn although it is not easily ignited. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

**Combustion Products:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of: Nitrogen.

## 6. ACCIDENTAL RELEASE INFORMATION

**Protective Measures:** Eliminate all sources of ignition in vicinity of spilled material.

**Spill Management:** Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

**Reporting:** Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at (800) 424-8802 as appropriate or required.

## 7. HANDLING AND STORAGE

**Precautionary Measures:** Liquid can evaporate and form vapor (fumes) which can catch fire and burn with explosive force. Vapor spreads easily and can be set on fire by many sources such as pilot lights, welding equipment, and electrical motors and switches. Hazard is greater as liquid temperature rises above 85F. Keep out of the reach of children.

**General Handling Information:** Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

**Static Hazard:** Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating an accumulation of electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids', National Fire Protection Association (NFPA 77, 'Recommended Practice on Static Electricity', and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents'.

**General Storage Information:** DO NOT USE OR STORE near heat, sparks or open flames. STORE ONLY IN WELL VENTILATED AREA. Keep container closed when not in use.

**Container Warnings:** Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks,

static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

## 8. EXPOSURE CONTROL/PERSONAL PROTECTIVE EQUIPMENT

### GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 3), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Special note: Do not use in breathing air apparatus or medical equipment.

### ENGINEERING CONTROLS:

Use in a well-ventilated area.

### PERSONAL PROTECTIVE EQUIPMENT

**Eye/Face Protection:** No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

**Skin Protection:** No special protective clothing is normally required. Where splashing is possible, select protective clothing depending on operations conducted, physical requirements and other substances in the workplace. Suggested materials for protective gloves include: 4H (PE/EVAL), Nitrile Rubber, Silver Shield, Viton.

**Respiratory Protection:** No respiratory protection is normally required.

If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge.

Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

### Occupational Exposure Limits:

Component	Agency	TWA	STEL	Ceiling	Notation
Highly refined mineral oil (C15 - C50)	ACGIH	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>		

Highly refined mineral oil (C15 - C50)	OSHA Z-1	5 mg/m <sup>3</sup>			
Aliphatic Hydrocarbons	OSHA PEL	350 mg/m <sup>3</sup>	1000 mg/m <sup>3</sup>		

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

**Appearance and Odor:** Brown or Blue liquid.

**Vapor Pressure:** <0.2 mmHg @ 100°F

**Vapor Density (Air = 1):** 5.2

**Boiling Point:** >400 °F (204 °C)

**Solubility:** Soluble in hydrocarbons; insoluble in water

**Freezing Point:** NA

**Melting Point:** NA

**Specific Gravity:** 0.865 @ 15.6 °C / 15.6 °C

**Viscosity:** >30 cSt @ 40 °C (Typical)

## 10. STABILITY AND REACTIVITY

**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Incompatibility With Other Materials:** May react with strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

**Hazardous Decomposition Products:** Hydrogen Sulfide (Temperatures >167 °F (75 °C))

**Hazardous Polymerization:** Hazardous polymerization will not occur.

## 11. TOXICOLOGICAL INFORMATION

**IMMEDIATE HEALTH EFFECTS**

**Eye Irritation:** The eye irritation hazard is based on evaluation of data for similar materials or product components.

**Skin Irritation:** The skin irritation hazard is based on evaluation of data for similar materials or product components.

**Skin Sensitization:** No product toxicology data available.

**Acute Dermal Toxicity:** The acute dermal toxicity hazard is based on evaluation of data for similar materials or product components.

**Acute Oral Toxicity:** The acute oral toxicity hazard is based on evaluation of data for similar materials or product components.

**Acute Inhalation Toxicity:** The acute inhalation toxicity hazard is based on evaluation of data for similar materials or product components.

**ADDITIONAL TOXICOLOGY INFORMATION:**

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as: carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B). These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

**12. ECOLOGICAL INFORMATION****ECOTOXICITY**

The toxicity of this material to aquatic organisms has not been evaluated. Consequently, this material should be kept out of sewage and drainage systems and all bodies of water.

**ENVIRONMENTAL FATE**

This material is not expected to be readily biodegradable.

**13. DISPOSAL INFORMATION**

Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods. (See B.C. Reg. GY/92 Waste Management Act; R.R.O. 1990, Reg. 347 General-Waste Management; C.C.S.M.c. W40 The Waste Reduction and Prevention Act; N.S. Reg. 51/95 and N.S. Reg. 179/96 for examples of Provincial legislation.)

**14. TRANSPORTATION INFORMATION**

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

**DOT Shipping Name:** PETROLEUM PRODUCTS, N.O.S.

**DOT Hazard Class:** NA

**DOT Identification Number:** NA

**DOT Packing Group:** NA

**15. REGULATORY INFORMATION**

<b>SARA 311/312 CATEGORIES:</b> (Acute) Health Effects:	NO
Delayed (Chronic) Health Effects:	NO
Fire Hazard:	NO
Release of Pressure Hazard:	NO
Reactivity Hazard:	NO

**REGULATORY LISTS SEARCHED:**

4_11=IARC Group 1	12=TSCA Section 8(a) PAIR	21=TSCA Section 5(a)
4_12A=IARC Group 2A	13=TSCA Section 8(d)	25=CAA Section 112 HAPs
4_12B=IARC Group 2B	15=SARA Section 313	26=CWA Section 311
05=NTP Carcinogen	16=CA Proposition 65	28=CWA Section 307
06=OSHA Carcinogen	17=MA RTK	30=RCRA Waste P-List
09=TSCA 12(b)	18=NJ RTK	31=RCRA Waste U-List

10=TSCA Section 4

19=DOT Marine Pollutant

32=RCRA Appendix VIII

11=TSCA Section 8(a) CAIR

20=PA RTK

The following components of this material are found on the regulatory lists indicated.

Aliphatic Hydrocarbons

17, 18, 20

**CHEMICAL INVENTORIES:**

UNITED STATES: All of the components of this material are on the Toxic Substances Control Act (TSCA) Chemical Inventory.

**NEW JERSEY RTK CLASSIFICATION:**

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows:

PETROLEUM OIL

**WHMIS CLASSIFICATION:** NA**16. DISCLAIMER****NFPA RATINGS:** Health: 1 Flammability: 2 Reactivity: 0**HMIS RATINGS:** Health: 1 Flammability: 2 Reactivity: 0

(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, \*-Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

**REVISION STATEMENT:** Revision updates many sections and the MSDS should be read in its entirety.

**ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:**

TLV - Threshold Limit Value

TWA - Time Weighted Average

STEL - Short-term Exposure Limit

PEL - Permissible Exposure Limit

CHA - Champion LLC

CAS - Chemical Abstract Service Number

NDA - No Data Available

NA - Not Applicable

&lt;= - Less Than or Equal To

&gt;= - Greater Than or Equal To

Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the ANSI MSDS Standard (Z400.1) by Champion LLC, 1001 Golden Drive, Clinton, Missouri 64735.

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best knowledge of Champion Brands, L.L.C. Champion Brands, L.L.C., makes no warranty whatsoever expressed or implied of merchantability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. Champion Brands, L.L.C., assumes no legal responsibility for use or reliance upon this data. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.