Permatex, Inc. 10 Columbus Blvd. Hartford, CT 06106 USA Telephone: 1-87-Permatex (877) 376-2839 Emergency: 800-255-3924 International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name:MEDIUM STRENGTH THREADLOCKER BLUE 6MLItem No:24200Product Type:Anaerobic

2. COMPOSITION/INFORMATION ON INGREDIENTS					
Component	Weight%	ACGIH TLV: TWA	OSHA PEL:		
POLYGLYCOL DIMETHACRYLATE 25852-47-5	60-80	Not Listed	Not Listed		
POLYGLYCOL OLEATE 9004-96-0	20-40	Not Listed	Not Listed		
TREATED SILICON DIOXIDE, SYNTHETIC, CRYSTALLINE-FREE 67762-90-7	<5	10 mg/m ³ total dust TLV	10 mg/m³ total dust		
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<3	Not Listed	Not Listed		
SACCHARIN 81-07-2	0.5-2.0	10mg/m ³ nuisance dust	Not Listed		
TITANIUM DIOXIDE 13463-67-7	0.1-1.0	10 mg/m ³ TWA ACGIH	15 mg/m ³ TWA (total dust)		

3. HAZARDS IDENTIFICATION

Toxicity:

At elevated temperatures may cause irritation of the respiratory tract. Irritates mucous membranes. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. High concentrations may cause central nervous system (CNS) depression. May cause eye and skin irritation. May cause skin sensitization. Note: This product does not contain microcyrstalline silica. Eye and skin contact, ingestion, inhalation

Primary Routes of Entry: Signs and Symptoms of Exposure:

Repeated skin contact may cause allergic skin reactions. Skin redness. Ingestion may cause nausea and vomiting. Inhalation overexposure may cause irritation, coughing and flu-like symptoms. May cause pain, redness or swelling of the eyes and excessive blinking and tear production.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
SACCHARIN 81-07-2	0.5-2.0	Delisted April 2000		Group 3: Vol 73, Page 517: 1999
TITANIUM DIOXIDE 13463-67-7	0.1-1.0	male rat-negative, female rat-negative, male mice-negative, female mice-negative	A4	Group 2B; Vol 93,2006; Vol 47,1989

Medical Conditions Recognized as Being Aggravated by Exposure:

Preexisting skin disorders.

4. FIRST AID MEASURES

Ingestion: Inhalation: Skin Contact: Eye Contact: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention. Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention. Wash off with soap and water. If skin irritation persists, call a physician. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): Recommended Extinguishing Media: >200°F Water fog, carbon dioxide, foam, dry chemical.

5. FIRE FIGHTING MEASURES

Special Fire-Fighting Procedures:

Hazardous Products of Combustion: Unusual Fire/Explosion Hazards: Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Oxides of carbon Closed containers may rupture or explode when exposed to extreme heat. May polymerize exothermically.

Lower Explosive Limit: Upper Explosive Limit:

Not determined Not determined

6. ACCIDENTAL RELEASE MEASURES Spill Procedures: Maintain good ventilati

Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

ORAGE Store away from heat. Store away from water or moisture. Protect from contamination. Keep containers tightly closed in a cool, well-ventilated place.

Handling:

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	Safety glasses	
Skin:	Rubber or plastic gloves.	
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.	
Respiratory Protection:	An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.	

Avoid prolonged skin contact. Keep away from eyes.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Blue liquid
Odor:	MILD
Boiling Point:	>300°F
pH:	Does not apply
Solubility in Water:	Insoluble
Specific Gravity:	1.1
VOC Content(Wt.%):	<2% by weight
Vapor Pressure:	Not determined
Vapor Density (Air=1):	>1 (air = 1)
Evaporation Rate:	Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Hazardous Polymerization: Incompatabilities:

Conditions to Avoid: Hazardous Products of Combustion:

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:Disposal should be made in accordance with federal, state and local regulations.US EPA Waste Number:NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Stable at normal conditions MAY OCCUR. Strong oxidizers, free radical initiators, inert gases, Peroxides, Reducing agents, Oxygen scavengers Heat Oxides of carbon

14. TRANSPORTATION INFORMATION

Domestic Ground Transport

DOT Shipping Name:	Unrestricted	
Hazard Class:	None	
UN/ID Number:	None	
Marine Pollutant:	None	

IATA

Proper Shipping Name:	Not regulated
Class or Division:	None
UN/NA Number:	None

IMDG

Proper Shipping: Hazard Class: UN Number: Unrestricted None None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

DIMETHYLBENZYL HYDROPEROXIDE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating:HEALTH 2, FLAMMABILITY 1, REACTIVITY 1Estimated HMIS Classification:HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0NFPA is a registered trademark of the National Fire Protection Assn.HMIS is a registered trademark of the National Paint and Coatings Assn.

 Prepared By:
 Denise Boyd, Health and Safety Manager
 Revision Date: August/13/2007

 Company:
 Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA 06106
 Revision
 1

 Number:
 Number:
 Number: