

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924  
 International Emergency: 813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** THE RIGHT STUFF GASKET MAKER 5 FL.OZ  
**Item No:** 29208  
**Product Type:** Elastomeric rubber

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
CALCIUM CARBONATE 471-34-1	25-50	10 mg/m <sup>3</sup> particulate TWA	Not Listed
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	20-40	Not Listed	Not Listed
POLYDIMETHYLSILOXANE 63148-62-9	5-20	Not Listed	Not Listed
VINYL OXIMINOSILANE 2224-33-1	1-10	Not Listed	Not Listed
STEARIC ACID 57-11-4	1-10	Not Listed	Not Listed
CARBON BLACK 1333-86-4	0.5-5.0	3.5 mg/m <sup>3</sup> TWA	3.5 mg/m <sup>3</sup> TWA
MODIFIED SILICON DIOXIDE 68611-44-9	0.5-5.0	Not Listed	Not Listed
2-BUTANONE OXIME 96-29-7	****	Not Listed	Not Listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye and skin irritation. May irritate lips, gums, tongue, mouth, nose and throat. May be harmful if swallowed. \*\*\*\*When this product is exposed to moisture, up to 10% methyl ethyl ketoxime may be formed. Note: This product does not contain microcrystalline silica.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Methyl ethyl ketoxime produced during cure is toxic and irritates eyes, nose and throat. Overexposure may cause eye and skin redness.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
CARBON BLACK 1333-86-4	0.5-5.0		Group A4 - Not classifiable as a human carcinogen	Group 2B; Monograph 65, 1996

**Medical Conditions Recognized as Being Aggravated by Exposure:** None known.

### 4. FIRST AID MEASURES

**Ingestion:** Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.

**Skin Contact:** Wipe off paste with paper towel or cloth. Wash off with soap and water. If skin irritation persists, call a physician.

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

### 5. FIRE FIGHTING MEASURES

**Flash Point (°F/C):** >200°F TCC

**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.

**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus.

**Hazardous Products of Combustion:** Formaldehyde, Silica fume, Oxides of carbon

## **5. FIRE FIGHTING MEASURES**

**Unusual Fire/Explosion Hazards:** None.

**Lower Explosive Limit:** Not determined

**Upper Explosive Limit:** Not determined

## **6. ACCIDENTAL RELEASE MEASURES**

**Spill Procedures:** Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

## **7. HANDLING AND STORAGE**

**Storage:** Store in a dry area below 90 degrees F. Keep container closed when not in use.

**Handling:** Avoid contact with skin and eyes. Do not inhale vapors.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eyes:** Safety glasses

**Skin:** Rubber or plastic gloves.

**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

**Respiratory Protection:** Not required under normal use. An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

**Comments:** When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Black paste

**Odor:** MILD

**Boiling Point:** Not applicable, polymeric material

**pH:** 7-8

**Solubility in Water:** Polymerized

**Specific Gravity:** 1.34

**VOC Content(Wt.%):** 5.3% by weight

**Vapor Pressure:** <5 mmHg @ 70°F

**Vapor Density (Air=1):** 3.0

**Evaporation Rate:** Slower than butyl acetate

## **10. STABILITY AND REACTIVITY**

**Chemical Stability:** Stable at normal conditions

**Hazardous Polymerization:** WILL NOT OCCUR.

**Incompatibilities:** Strong oxidizers, Polymerized by contact with moisture

**Conditions to Avoid:** Exposure to moisture

**Hazardous Products of Combustion:** Formaldehyde, Silica fume, Oxides of carbon

## **11. TOXICOLOGICAL INFORMATION**

See Section 3

## **12. ECOLOGICAL INFORMATION**

No data available

## **13. DISPOSAL CONSIDERATIONS**

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.

**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

## **14. TRANSPORTATION INFORMATION**

**DOT (49CFR 172)**

**Domestic Ground Transport**

**Product Name:** THE RIGHT STUFF GASKET MAKER 5  
FL.OZ

**Item No:** 29208

**DOT Shipping Name:** Unrestricted  
**Hazard Class:** None  
**UN/ID Number:** None  
**Marine Pollutant:** None

**IATA**

**Proper Shipping Name:** Not regulated  
**Class or Division:** None  
**UN/NA Number:** None

**IMDG**

**Proper Shipping:** Unrestricted  
**Hazard Class:** None  
**UN Number:** None

**15. REGULATORY INFORMATION**

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

**CALIFORNIA PROP 65:**

No California Prop 65 chemicals are known to be present.

**TSCA Inventory Status:**

**Listed on Inventory:** YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

**16. OTHER INFORMATION**

**Estimated NFPA Rating:** HEALTH 1, FLAMMABILITY 1, REACTIVITY 0

**Estimated HMIS Classification:** HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Health and Safety Manager  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** January/12/2007  
**Revision Number:** 5