

ACCESSORIES

LOG CATCHERS

S40200600 22-TON

S40200600 28-TON (before serial number: 1G1110553)

564068 28-TON (after serial number: 1G1110552)

Log catchers keep work at a consistent height, reducing strain and fatigue on the operator and help keep the immediate work-space in order. Built of heavy gauge steel, these attachments are designed to be durable and easily installed.



4-WAY WEDGE

S40201200 22-TON

S40201200 28-TON (before serial number: 1G1110553)

564066 28-TON (after serial number: 1G1110552)

Make quick work of larger diameter logs with this 4-way splitter. The quick release cotter pin makes change out with the standard wedge effortless.



LOG SPLITTERS

Fast cycle times with a full range of features.





MODELS

6-TON

S40100600

This highly portable splitter is ideal for indoor or outdoor use. Powered by standard 120v electricity, the 15 amp motor is a clean and powerful choice for home owners and outdoor enthusiasts.

22-TON

S402022H0

S402022K0

The most popular category on the market, the 22-ton splitter is capable of handling most jobs with ease. Efficiently sized, this unit combines resilience with maneuverability.

28-TON

S402028H0

S402028K0

Loaded with a full range of features including a high-volume pump, large wheels, heavy-duty beam, and extreme hydraulic force make this splitter ready for the toughest jobs.



WARRANTY

3 years on all steel components;
2 years engine (as rated by manufacturer);
1 year on all hydraulics



KOHLER SH265

HONDA GC190

WARRANTY

3 years on all steel components;
2 years engine (as rated by manufacturer);
1 year on all hydraulics



196CC

190CC



KOHLER CH395

HONDA GX270

WARRANTY

3 year on all steel components;
3/2 years engine (as rated by manufacturer);
1 year on all hydraulics



277CC

270CC

SPECIFICATIONS

	Operation	Motor	Max. PSI	Cylinder	Pump	Hydraulic Capacity	Auto-Return Valve	Cycle Time	Stripper Plates	Log Capacity	Log Cradle	Working Height	Beam	Wedge	Weight	Tires/Wheels
6-TON	Horizontal	120V, 60HZ, 15A, 2HP (3,400 RPM/ Copper Windings)	2300	2.2" x 15.2"	1 Stage	2.8 Quarts	✓	25 Sec.	✗	20"	✓	14.5"	3.25" x 5.25"	4.5"	106 lbs.	6.5" Wheel
22-TON	Horizontal & Vertical	Kohler SH265 or Honda GC190	—	4" x 24"	2 Stage, 11 GPM	24 Quarts	✓	13 Sec.	✓	24"	✓	31.5"	6" x 6"	8"	595 lbs.	4.80" x 8" DOT Certified Tire
28-TON	Horizontal & Vertical	Kohler CH395 or Honda GX270	—	4.5" x 24"	2 Stage, 16 GPM	26 Quart	✓	11.5 Sec.	✓	24"	✓	33"	6.5" x 8"	8"	680 lbs.	4.80" x 12" DOT Certified Tire