

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: MEDIUM STRENGTH THREADLOCKER BLUE GEL 10 GR
Item No: 24010
Product Type: Anaerobic

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredient | Weight Percent | ACGIH TLV: | OSHA PEL: |
|---|----------------|-------------------------------------|---------------------------------------|
| POLYGLYCOL DIMETHACRYLATE 25852-47-5 | 35-45 | Not Listed | Not Listed |
| POLYESTER RESIN MIXTURE | 15-25 | Not Listed | Not Listed |
| BENZOATE ESTERS MIXTURE | 15-25 | Not Listed | Not Listed |
| TREATED SILICON DIOXIDE, SYNTHETIC, CRYSTALLINE-FREE 67762-90-7 | 1-10 | 10 mg/m ³ total dust TLV | 10 mg/m ³ total dust |
| DIMETHYLBENZYL HYDROPEROXIDE 80-15-9 | <3 | Not Listed | Not Listed |
| PROPYLENE GLYCOL 57-55-6 | <3 | Not Listed | Not Listed |
| POLYAMIDE WAX MIXTURE | <3 | Not Listed | Not Listed |
| TITANIUM DIOXIDE 13463-67-7 | 0.1-1.0 | 10 mg/m ³ TWA ACGIH | 15 mg/m ³ TWA (total dust) |

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. At elevated temperatures may cause irritation of the respiratory tract. Irritates mucous membranes. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. High concentrations may cause central nervous system (CNS) depression. May cause skin sensitization. Note: This product does not contain microcrystalline silica.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Repeated skin contact may cause allergic skin reactions. Skin redness. Ingestion may cause nausea and vomiting. Inhalation overexposure may cause irritation, coughing and flu-like symptoms. May cause pain, redness or swelling of the eyes and excessive blinking and tear production.

| Ingredient | Weight Percent | NTP | ACGIH Carcinogens | IARC |
|--------------------------------|----------------|---|-------------------|------------------------------------|
| TITANIUM DIOXIDE 13463-67-7 | 0.1-1.0 | male rat-negative, female rat-negative, male mice-negative, female mice-negative | A4 | Group 2B; Vol 93,2006; Vol 47,1989 |

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting skin disorders.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): More than 200 degrees C. Method: PMCC

5. FIRE FIGHTING MEASURES

Recommended Extinguishing Media:

Water fog, carbon dioxide, foam, dry chemical.

Special Fire-Fighting Procedures:

Firefighters should wear self-contained breathing apparatus.

Hazardous Products of Combustion:

Irritating vapors

Unusual Fire/Explosion Hazards:

Closed containers may rupture or explode when exposed to extreme heat.

Lower Explosive Limit:

Not determined

Upper Explosive Limit:

Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

Store below 100 degrees F.

Handling:

Avoid prolonged skin contact. Keep away from eyes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses

Skin:

Rubber or plastic gloves.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection:

An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Blue gel

Odor:

MILD

Boiling Point:

More than 150 degrees C.

pH:

Does not apply

Solubility in Water:

Insoluble

Specific Gravity:

>1.0

VOC Content(Wt.%):

Not determined

Vapor Pressure:

Not determined

Vapor Density (Air=1):

Heavier than air

Evaporation Rate:

Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

WILL NOT OCCUR.

Incompatibilities:

Strong oxidizers, free radical initiators, inert gases.

Conditions to Avoid:

Heat

Hazardous Products of Combustion:

Irritating vapors

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:

Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number:

NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name:

Unrestricted

Product Name: MEDIUM STRENGTH THREADLOCKER
BLUE GEL 10 GR

Item No: 24010

Hazard Class: None
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Not regulated
Class or Division: None
UN/NA Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

DIMETHYLBENZYL HYDROPEROXIDE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 1

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: 12/13/2006
Revision Number: 3